

AMBRA UNITEK 10W-40 Cod. 2755

DESCRIPTION

Synthetic-based lubricant for new generation low emission engines of tractors, other agricultural and earth moving machinery.

CHARACTERISTICS

Due to the use of high performance bases and additives as they are accurately selected for their high quality level, PETRONAS LUBRICANTS has created a formula that fully meets the stringent technical requirements of CNH that has assigned AMBRA UNITEK the MAT 3521 specification. In particular this lubricant can boast:

- | > a TBN of 10 against decidedly lower values of standard API CJ-4 level engine oils. The TBN is an index of the capability of the lubricant to neutralize the acids that form with the products of combustion when the engine is running and which would cause damage to its components
- | > a very high resistance to oxidation (oxidation stability).
- | AMBRA UNITEK optimizes the protection of the DPF filter (Diesel Particulate Filter) keeping its efficiency high and preserving its life due to particular additives and the low volatility of the lubricant bases.
- | AMBRA UNITEK is perfectly usable also for engines fitted with other exhaust gas aftertreatment or recirculation systems or for engine with conventional technology.
- | In addition to the above-mentioned reasons, AMBRA UNITEK has obtained the official technical approval of CNH also following stringent, very intensive bench and field tests that were prolonged for many working hours under severe operating conditions, in many areas of the world.
- | Because of its SAE 10W-40 viscosity grade, this lubricant considerably improves engine starting at low temperatures (startability). The environment temperature range in which it can be used has been broadened and is the following: from -25°C to + 40 °C.



ADVICE ON USE

Drain interval according to the Manufacturer's instructions.
Can be used for environment temperatures between -25°C and + 40 °C.

TECHNICAL DATA

SAE 10W-40, MAT 3521, API CJ-4, ACEA E7/E9,
MB-Approval 228.31, CUMMINS CES 20081,
Cat ECF-3/ ECF-2/ECF-1