

TECHNICAL CHARACTERISTICS

AGRICOIL UTTO

PRODUCT CODE: 140Z

APPLICATION

Multipurpose UTTO lubricant specifically for transmissions, hydraulic systems and wet brakes of tractors, farm machines and earthmoving machinery.

SPECIFICATIONS

SAE 10W-30, API GL 4, ISO VG 32/46, ZF TE-ML 03E, ZF TE-ML 05F, ZF TE-ML 17E, ZF TE-ML 21F, MF M1135, M1110, M1141, M1145, M1143, M1127A/B, M1129A Performance, ALLISON C4 Performance, CAT TO-2 Performance, JD J20C Performance, DENISON HF-0/HF-1/HF-2 Performance

TEST DESCRIPTION

TEST DESCRIPTION	METHOD	UNIT	TYPICAL VALUE
APPEARANCE	--	--	B. & C.
COLOUR	--	--	L3
DENSITY AT 15°C	ASTM D4052	g/cm ³	0,885
VISCOSITY AT 100°C	ASTM D445	cSt	9,5
VISCOSITY INDEX	ASTM D2270	--	147
VISCOSITY @ -25°C	ASTM D 5293	cPs	6000
FLASH POINT CI. O. C.	ASTM D92	°C	210
POUR POINT	ASTM D97	°C	<-40
FOAM AT 24°C	ASTM D892	cc/s	10

All technical data is provided for reference only.

RESEARCH & DEVELOPMENT

05/2015