



PETRONAS

CARACTERISTICI TEHNICE

ARBOR ALFAPRIME 10W-30

CODUL PRODUSULUI: 3636

APLICARE

Low SAPS lubricant for the new generation low emission engines for tractors, other farming and earthmoving machines, including those equipped with with exhaust gas re-circulation or after treatment systems (EGR, SCR, diesel particulate filter DPF). Suitable for engines with traditional older technology.

SPECIFICAȚII

SAE 10W-30, API CJ-4, ACEA E7/E9, Caterpillar ECF-3 / ECF-2 / ECF-1a, DAF Euro VI, DETROIT DIESEL 93K218, MACK EO-O PREMIUM PLUS-07, MAN M3575, MB-Approval 228.31 Performance, RENAULT RVI RLD-3

DESCRIEREA TESTULUI

DESCRIEREA TESTULUI	METODĂ	UNITATE	VALOARE TIPICĂ
ASPECT	--	--	C & B
DENSITATE 15°C	ASTM D 4052	g/cm ³	0,868
VISCOSITA' @ 100°C	ASTM D 445	cSt	12.1
INDICE DE VÂSCOZITATE	ASTM D 2270	--	143
T.B.N. (t-Butil Nitrit)	ASTM D 2896	mg KOH/g	9,6
PUNCT DE INFLAMABILITATE CI. O. C.	ASTM D 92	°C	>200
TEMPERATURĂ DE CONGELARE	ASTM D 97	°C	<-33
SPUMĂ @ 24°C	ASTM D 892	cc/s	0 / 0

Toate datele tehnice au numai rol de referință.

CERCETARE ȘI DEZVOLTARE

06/2019