



PETRONAS

CARACTERISTICI TEHNICE

ARBOR ALFAPRIME 15W-40

CODUL PRODUSULUI: 3637

APLICARE

Low SAPS lubricant for the new generation low emission engines for tractors, other farming and earthmoving machines, including those equipped with with exhaust gas re-circulation or after treatment systems (EGR, SCR, diesel particulate filter DPF). Suitable for engines with traditional older technology.

SPECIFICAȚII

SAE 15W-40, API CJ-4, ACEA E7/E9, Caterpillar ECF-3 / ECF-2 / ECF-1a, CUMMINS CES 20081, DETROIT DIESEL 93K218, DEUTZ DQC III-10-LA, MACK EO-O PREMIUM PLUS-07, MAN M3575, MB-Approval 228.31 Performance, RENAULT RVI RLD-3

DESCRIEREA TESTULUI

DESCRIEREA TESTULUI	METODĂ	UNITATE	VALOARE TIPICĂ
ASPECT	--	--	C & B
DENSITATE 15°C	ASTM D 4052	g/cm ³	0,878
VÂSCOZITATE @ 100°C	ASTM D 445	cSt	15.4
INDICE DE VÂSCOZITATE	ASTM D 2270	--	135
T.B.N. (t-Butil Nitrit)	ASTM D 2896	mg KOH/g	9.1
PUNCT DE INFLAMABILITATE CI. O. C.	ASTM D 92	°C	>200
TEMPERATURĂ DE CONGELARE	ASTM D 97	°C	<-27
SPUMĂ @ 24°C	ASTM D 892	cc/s	0 / 0

Toate datele tehnice au numai rol de referință.

CERCETARE ȘI DEZVOLTARE

06/2019