



## **TECHNICAL CHARACTERISTICS**

**HYDRA 68**

**PRODUCT CODE: 182Z**

### **APPLICATION**

Antiwear hydraulic oil for mobile equipment, earth moving machines and independent hydraulic system of agricultural tractor.

### **SPECIFICATIONS**

ISO VG 68, DIN 51524 HLP 68 Performance, DENISON HF-0 Performance

### **TEST DESCRIPTION**

| TEST DESCRIPTION      | METHOD     | UNIT              | TYPICAL VALUE |
|-----------------------|------------|-------------------|---------------|
| APPEARANCE            | --         | --                | B. & C.       |
| COLOUR                | --         | --                | L 1,5         |
| DENSITY AT 15°C       | ASTM D4052 | g/cm <sup>3</sup> | 0,880         |
| VISCOSITY AT 40°C     | ASTM D445  | cSt               | 68,4          |
| VISCOSITY AT 100°C    | ASTM D445  | cSt               | 9,1           |
| VISCOSITY INDEX       | ASTM D2270 | --                | 102           |
| FLASH POINT Cl. O. C. | ASTM D92   | °C                | 220           |
| POUR POINT            | ASTM D97   | °C                | -33           |

All technical data is provided for reference only.

RESEARCH & DEVELOPMENT

06/2015