



TECHNICAL CHARACTERISTICS

HERCULES HD-7

PRODUCT CODE: 125Z

APPLICATION

Multigrade diesel engine oil for trucks with turbo diesel and naturally aspirated engines. Specifically developed for new engines. It complies with the requirements of Euro Emission Standards.

SPECIFICATIONS

SAE 15W-40, API CI-4, ACEA E7, CAT ECF-1 Performance,
CUMMINS CES 20076/20077 Performance, MACK EO-N Performance, MAN M3275 Performance,
MB 228.3 Performance, MTU OIL TYPE 2 PERFORMANCE, RENAULT VI RLD-2 Performance,
VOLVO VDS-3 Performance

TEST DESCRIPTION

TEST DESCRIPTION	METHOD	UNIT	TYPICAL VALUE
APPEARANCE	--	--	B. & C.
DENSITY AT 15°C	ASTM D4052	g/cm ³	0,885
VISCOSITY AT 100°C	ASTM D445	cSt	14,6
VISCOSITY INDEX	ASTM D2270	--	135
FLASH POINT CI. O. C.	ASTM D92	°C	> 210
T.B.N.	ASTM D2896	mg KOH/g	11,5
POUR POINT	ASTM D97	°C	< - 27
FOAM AT 24°C	ASTM D892	cc/s	TRACES/0

All technical data is provided for reference only.

RESEARCH & DEVELOPMENT

09/2015