

**CARACTERISTICI TEHNICE**  
**TUTELA TRANSMISSION STARGEAR**  
**CODUL PRODUSULUI: 2285**

**APLICARE**

Lubricant for synchronized manual transmissions and non-car and commercial vehicles formulated with carefully selected mineral bases.  
STARGEAR protection provides an excellent protection against corrosion and wear in the most difficult working conditions

**SPECIFICAȚII**

SAE 80W, API GL 4, MB-Approval 235.1, ZF TE-ML 02B, ZF TE-ML 17A, MAN 341 Type E1, MAN 341 Typ Z2

**DESCRIEREA TESTULUI**

DESCRIEREA TESTULUI	METODĂ	UNITATE	VALOARE TIPICĂ
ASPECT	--	--	B&C
CULOARE	--	--	AMBER
DENSITATE 15°C	ASTM D 4052	g/cm <sup>3</sup>	0.885
VISCOSITA' @ 100°C	ASTM D 445	cSt	10.7
VÂSCOZITATE @ 40°C	ASTM D 445	cSt	91
INDICE DE VÂSCOZITATE	ASTM D 2270	--	101
VÂSCOZITATE @ -26°C	ASTM D 2983	cPs	81000
TEMPERATURĂ DE CONGELARE	ASTM D 97	°C	-27
PUNCT DE INFLAMABILITATE CI. O. C.	ASTM D 92	°C	210
PUNCT DE FIERBERE	ASTM D 1120	°C	>250
COROZIUNE PE PLACĂ DE CUPRU (3h/150°C)	ASTM D 130	--	1b
SPUMĂ @ 24°C	ASTM D 892	cc/s	Traces/0

Toate datele tehnice au numai rol de referință.