



PETRONAS

CARACTERISTICI TEHNICE

ARBOR UNIVERSAL 10W-40

CODUL PRODUSULUI: 3638

APLICARE

Universal lubricant (S.T.O.U.) for engines, transmissions, hydraulic systems and wet brakes of agricultural and construction machinery.

SPECIFICAȚII

SAE 10W-40, SAE 75W-90, ISO VG 32/46, API GL 4, ACEA E//E4 Performance, ZF-TE-ML-06B, ZF TE-ML 06F, ZF TE-ML 07B, MIL-L-2105 Performance

DESCRIEREA TESTULUI

| DESCRIEREA TESTULUI | METODĂ | UNITATE | VALOARE TIPICĂ |
|------------------------------------|---------------|-------------------|-----------------------|
| ASPECT | -- | -- | B.&C. |
| DENSITATE 15°C | ASTM D 4052 | g/cm ³ | 0,863 |
| VISCOSITA' @ 100°C | ASTM D 445 | cSt | 14,1 |
| INDICE DE VÂSCOZITATE | ASTM D 2270 | -- | 160 |
| VÂSCOZITATE @ -25°C | ASTM D 5293 | cPs | 5700 |
| PUNCT DE INFLAMABILITATE CI. O. C. | ASTM D 92 | °C | 210 |
| TEMPERATURĂ DE CONGELARE | ASTM D 97 | °C | <-30 |

Toate datele tehnice au numai rol de referință.

CERCETARE ȘI DEZVOLTARE

12/2012